

VCS NAA

VCS NA-A is a powerful, low-sludging antioxidant which provides excellent stability in petroleum products. It is an especially cost effective liquid antioxidant used in applications such as Turbine oils, Compressor oils, Quenching and Hydraulic oils. It is a high performance antioxidant which has excellent free radical scavenging abilities in a wide variety of base stocks including mineral, hydro-treated, synthetic and vegetable oils.

Composition	Alkylated Phenyl Alpha Naphthylamine
EC no.:	437-450-6

TYPICAL CHARACTERISTICS

Property	Unit	Typical Value	Test Method
Appearance	-	Brown liquid	Visually
Refractive Index (@ 25°C)	-	1.5500 – 1.6500	QCD/TM/76
Density (@ 25°C)	gm/cm ³	0.9900 – 1.0100	ASTM D 1481
Flash Point	°C	220 - 290	ASTM D 92 – 02b

RECOMMENDED BLENDING, HANDLING & STORAGE CONDITIONS

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

PACKAGING

Available in 200 Kg. Drum.

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

