

VCS PA 15 S

VCS PA 15 S is high molecular phenolic antioxidant used in hydraulic fluids, metalworking fluids, industrial gear oils, turbine oils, polyglycols, and use with natural and synthetic esters.

Composition	Thiodiethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propi
CAS No.	61484 -35-9
EC No.	255-392-8
Molecular Formula	C ₃₈ H ₅₈ O ₆ S
Molecular Weight	643

TYPICAL CHARACTERISTICS

Property	Unit	Typical Value	Test Method
Appearance	-	Crystalline white to yellow powder	
Melting point	°C	63.0 – 74.0 min.	ASTM D 1519
Moisture content	%	3.0 max.	ASTM E 1868
Ash content	%	0.1 max.	ASTM D 0874
Sulfur content	%	4.0 – 6.0	ASTM D 4951

RECOMMENDED BLENDING, HANDLING & STORAGE CONDITIONS

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

PACKAGING

Available in 25 Kg. Bag.

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

