

VCS TT 30

VCS TT 30 is used in Engine Oil, Compressor Oil, Turbine Oil, Gear Oil, Hydraulic Fluids.

Composition	N,N-Bis(2-ethylhexyl)-[(1,2,4-triazol-1-yl)methyl]amine
CAS No.	91273-04-0
EC No.	401-280-0
Molecular Formula	C ₁₉ H ₃₈ N ₄
Molecular Weight	322

TYPICAL CHARACTERISTICS

Property	Unit	Typical Value	Test Method
Appearance	-	Colorless to light yellow liquid	Visual
Active ingredient	%	100.0 min.	-
Density @15oC	g/cm ³	0.9105 - 0.9305	ASTM D 1481
Density @20oC	g/cm ³	0.900-0.940	ASTM D 1481
Flash point	°C	130.0 min.	ASTM D 92 - 02b
Viscosity @ 40oC	cSt	25.0 – 45.0	ASTM D 0445
Viscosity @ 100oC	cSt	2.0 – 6.0	ASTM D 0445
Nitrogen content	%	16.0 – 18.0	ASTM D 5291-10
Mineral Oil	%	0.00	QCD/TM/81
Specific gravity at 60/60 F	NA	0.900 - 0.931	QCD/TM/77
Refractive index @20°C	NA	1.465 -1.475	QCD/TM/76

RECOMMENDED BLENDING, HANDLING & STORAGE CONDITIONS

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

PACKAGING

Available in 200 Kg Drums.

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.

