

VCS SN 120

CHARACTERISTICS

		120 SN		
Test	Test Method	Min	Typical*	Max
Kinematic Viscosity cSt @ 40 °C cSt @ 100 °C	ASTM D445 ASTM D445	21.5 4.42	24.1 4.7	26.5 5.02
Viscosity Index	ASTM D2270	110	115	<120
Color	ASTM D1500	--	L 0.5	1.0
Appearance	Visual	--	Clear & Bright	--
Specific Gravity @ 15°C (60°F)	ASTM D4052	--	0.846	--
lb/gal		--	7.01	--
Flash Point, °C	ASTM D92	205	228	--
Pour Point, °C	ASTM D5950	--	-18	-15
Cold Cranking Simulator cP @ -20 °C cP @ -25 °C cP @ -30 °C	ASTM D5293 ASTM D5293 ASTM D5293	-- -- --	858 1496 2664	-- 2000 --
Evaporation Loss, NOACK, wt%	ASTM D5800	--	12.5	15.0
Sulfur, ppm	ASTM D5185	--	<50	<150

Note: * Typical and Min/Max Specs - Subject to change

NOTE: Values indicated are typical physical properties and are not specification limits. Seller offers no warranty, expressed or implied, concerning the suitability of this product for any particular purpose.



Learn More At www.VERTICALCHEMICAL.com
sales@verticalchemical.com



Made In U.S.A.